



Shop Order

Carrier Truck Center Inc.
 O/A Carrier Centers
 645 Athlone Place
 Woodstock, ON N4S 7V8

The Corporation of the Town of Aylmer
 46 Talbot Street West
 Aylmer, ON N5H 1J7

Sales Rep: Todd Finnie Carrier Truck Centers Inc.	Terms: Chassis, body and equipment COD with \$25,000.00 holdback for 90 days
Drawing #: FT-11046-FL-A	
Est. Delivery Date: / /	
Customer PO #: 20600	Penalty:
Customer #: 1560	None
QPF #:	

Quote No: Aylmer, ON-0511
Job/Order No: 20922
 10/06/2020

PART NO	QTY	DESCRIPTION
	1	== <i>Metalfab Pumper - ULC 05/13 - 0.000</i> ==
	1	CHANGE ORDER D
00-10-1520	1	Metalfab Pumper - Ontario unit
00-20-1000	1	Company Profile E
00-20-1500	1	Standard Body Warranty
00-20-1550	1	Metalfab Limited Ten (10) Year Paint and Corrosion Warranty
00-20-1600	1	Waterous Pump Warranty - 5 years
00-20-1800	1	Polypropylene Tank Lifetime Warranty
00-20-2100	1	Plant Inspection Visits - 1 visit for 2 reps for final inspection- Costs by CCEV
00-20-3000	1	No Bonding Requested
00-20-3500	1	Certification for Fusion Welding of Aluminum
00-20-4000	1	Quality System registered to ISO 9001:2015
00-20-4500	1	Fire Apparatus Manufacturers' Association Membership
	1	GENERAL INFORMATION
10-11-0000	1	Intent E
10-11-0110	1	Vehicle data recorder included with chassis
10-11-1101	1	ULC S515-13 and NFPA 1901-2016 Compliance E
10-11-1500	1	ULC Testing - Pumper Test in Imperial units.
10-11-2100	1	Maximum length not specified E
10-11-2200	1	Maximum height not specified E
10-11-2400	1	Overall length is 30' or more
10-11-2500	1	General Construction
10-11-2600	1	Preconstruction Meeting- by CCEV
10-11-3000	1	Manuals - two copies ***Two copies of manuals are required.
10-11-3600	1	Delivery - FOB Fire Department - by CCEV
10-11-4200	1	Payment Terms - Chassis and Body COD with \$25,000 holdback for 90 days
10-20-1000	1	Hose bed capacity - standard ULC Pumper
10-20-2000	1	Equipment carrying capacity - standard ULC Pumper
	1	CHASSIS INFORMATION
20-11-1010	1	Chassis supplied by Metalfab - Freightliner 4 door M2 106 350 HP, 1000 torque 41,600 lb GVWR 14,600 lb front axle 27,000 lb rear axle 248" wheelbase 135.21" cab to axle 90" overhang

PART NO	QTY	DESCRIPTION
		<p>Cummins L9 350 hp @ 2000 rpm 2200 governed rpm 1000 lb/ft torque @ 1400 rpm 3000 EVS automatic transmission, 5 speed, 275 amp alternator 189 litre fuel tank - left side under cab Manual windows and door locks ESC, VDR and seat/seatbelt display Color to be white over red - paint codes to be White Axalta P2512 EB and Red Axalta 498148 EB which were approved 08.19.2019 Paint dividing liner - Freightliner Emergency 6 - White starts at windshield (hood remains red) as approved by e-mail from Todd Finnie on 07.05.2019. ***Order chassis with pre-plumb for air horns and air horns shipped loose (these will be recessed in front bumper by Metalfab - ref 20-51-9001) - controls for air horn to be through steering wheel and push button on Officers side dash. ***Order chassis with aluminum wheels and trim ***Include Freightliner code 128-1AR for brake lights on with exhaust brake</p>
20-11-1500	1	2013 Emission chassis modifications
20-11-1700	1	Chassis Motor Vehicle Inspection required - by CCEV
20-21-0500	1	Fluid capacity plate
20-21-0600	1	Pumping test plate
20-21-1030	1	Maximum riders sign - 5 persons
20-21-1510	1	Seat belt warning labels - 4 door chassis
20-21-1520	4	Helmet warning label - do not wear helmet
20-21-1560	1	Tire Pressure Indicators - Single Axle
20-21-1600	1	Apparatus Information Label An information label is provided in the chassis cab, visible to the driver, stating: "When manufactured, this vehicle was: ** m high ** m long ** kg GVW Changes in height since the apparatus was manufactured shall be noted on this plate by the Fire Department"
20-21-2000	1	Non removable key
20-21-2500	1	Shifter lock not required E
20-21-3500	1	Rear step warning label
20-21-3810	1	Front mudflaps provided with chassis E
20-21-4000	1	Rear mudflaps - Metalfab Logo
20-31-0200	1	Fuel fill label -Ultra Low Sulfur Diesel only
20-31-1100	1	Alum tread fuel tank covers, diamond grip steps, Conv - 4 dr The step surfaces will be one (1) piece except on the upper driver side due to the fuel fill and DEF fill. As requested by Todd Finnie and customer.
20-31-1900	1	Chassis cab painted white over red by chassis OEM Color to be white over red - paint codes to be White Axalta P2512 EB and Red Axalta 498148 EB which were approved 08.19.2019
20-31-4700	1	Extend front bumper, gravshld with preconnected hosewell E ***Bumper to be extended approximately 20" ahead of cab. A hinged aluminum treadplate cover will be installed over the hosewell, complete with gas strut, lift and turn latch and a slot in the left side (driver's side) to accommodate fire hose to be pre-connected.
20-31-7500	1	Console in cab Install switch panel (50-11-0900), siren (50-11-1400), Generator control (50-31-40AA), radio blank (50-35-0500), and pump shift (30-51-0500) in console. Storage area with hinged cover and lift and turn latch provided at rear of console. ***Leave clearance for mounting of fire extinguisher at front*** Gray Zolatone finish.

PART NO	QTY	DESCRIPTION
20-41-0900	1	Auxiliary braking system disabled when pumping
20-41-1100	1	Transmission programming - Allison WT ***Includes "Pump Engaged" light next to pump shift on chassis instrument panel.
20-41-1500	1	Extend exhaust pipe - RS front of rear wheels E Includes Freightliner diffuser on end Engineering to specify exhaust pipe material as required by the chassis manufacturer. Engineering to sign off on the exhaust configuration to make sure it meets the chassis manufacturer's emission specifications.
20-41-1900	1	Battery boost terminals with chassis E Included with chassis
20-41-2000	1	Chassis batteries remain in OEM location
20-41-2510	1	Fuel fill at step fuel tank under cab
20-41-2600	1	Chassis fuel tank remains in OEM location
20-41-5000	1	Rear Tow Hooks - under body *** Flat bar tow hooks under rear step (2)
20-51-0710	1	Master Battery Disconnect included with Freightliner chassis
20-51-2500	1	Back up alarm included with chassis
20-51-3400	1	Protection valve installed for air operated accessories
20-51-4000	1	Auto eject for air inlet - LS Located on left side pump panel - this inlet is in addition to the Kussmaul compressor.
20-51-6200	7	120 volt 20 A shore line connection in chassis cab Standard 5-20R duplex receptacle in chassis cab, not fused Location of the receptacles to be: Receptacle #1-In cab for the battery conditioner to plug into Receptacle #2-Rear Centre of console 20-31-7500 Receptacle #3-Upper portion of L3 compartment Receptacle #4-Lower portion of R3 compartment - just below compartment depth change Receptacle #5-Upper portion of R1 compartment Receptacle #6-Upper portion of L1 compartment Receptacle #7-Upper portion of back compartment As requested by e-mail from Todd Finnie on 07.05.2019
20-51-6600	1	Kussmaul Pump Plus conditioner/compressor Battery conditioner is located under rear left seat and is to be protected with guard as requested by Todd Finnie by e-mail on 07.05.2019 Compressor is located inside pump house with easy access through the pump inspection door on right side
20-51-7101	1	Electric System Management - VMUX
20-51-7500	1	Super Auto eject for 120 v - 20 A with sealed enclosure Located on left side pump panel
20-51-8510	1	Engine compartment light LED One required each side to light up complete engine compartment Switched when hood is opened
20-51-9001	1	Air horns as supplied by chassis OEM Air horns are shipped loose with the chassis - Metalfab to install recessed in the front bumper and air horns will be controlled from the steering wheel and a push button on the officer's side of the cab dash.
20-52-3500	1	Chassis steering wheel lined up by Metalfab E
20-52-4000	1	Rear View Camera system Rearview Systems STM5600 with 5.6" colour monitor in cab mounted rigidly on center part of cab dash

PART NO	QTY	DESCRIPTION
20-60-0400	1	Chassis wheelbase does not change
	1	PUMP AND PLUMBING
30-12-4000	1	<i>Mechanical seals for Waterous pumps</i>
30-12-6000	1	<i>Waterous CSU single stage 1250 IGPM</i>
30-15-0204	1	<i>Plumbing - Waterous manifold pump SM SS E</i>
30-20-0500	1	Valves and controls - side mount panel
30-20-1001	1	Valve brand not specified E
30-20-1600	1	<i>Piping stainless steel - general</i>
30-20-1700	1	<i>1-1/2" thread specifications - NPSH</i>
30-20-1800	1	<i>2-1/2" thread specifications - CSA</i>
30-20-2000	1	<i>Piping hydrostatic test</i>
30-20-2500	1	<i>Anodes in suction and discharge piping</i> Install one anode on discharge side of pump, one anode on suction side of pump - do not use teflon tape or thread sealant. Paint flange silver and mask brass anode before painting for visibility.
30-21-5560	1	<i>Tank to Pump SS 3" w/ check valve manifold pump</i>
30-22-0520	1	<i>Tank Fill valve 2" SS</i>
30-31-4010	1	<i>Suction - 6" not gated each side manifold pump</i>
30-32-7535	1	<i>Suction - 2-1/2" left side SS, bleeder, Waterous manifold pump</i>
30-40-2025	1	<i>4" right discharge SS, plumbed 3", Waterous manifold pump</i> Slow-close required
30-40-25AA	1	<i>4" rear discharge, 3" valve and piping, bleeder, 4" 30° Storz connection</i> Slow-close required
30-41-2025	1	<i>2-1/2" RS discharge SS, bleeder, Waterous manifold pump</i>
30-41-2525	2	<i>2-1/2" LS discharge SS, bleeder, Waterous manifold pump</i>
30-44-0520	2	<i>1-1/2" crosslay (each) SS, 2" valve, bleeder</i> Capacity for minimum 200' x 1-3/4" hose and nozzle. Equipped with stainless steel rollers on each end.
30-44-1020	1	<i>1-1/2" front trash line SS, plumbed 2", hosewell</i> Capacity for minimum 150' x 1-3/4" hose and nozzle. Chrome swivel discharge elbow located left of hose well (driver's side)
30-44-6520	1	<i>Piping for monitor SS, plumbed 3", bleeder</i> Piping is centered in area behind the Crosslays and will extend approximately 1" above the pump house. The piping will be capped.
30-51-0500	1	<i>Pump shift-Midship air</i> ***Includes "Pump Engaged" and "OK to Pump" indicator lights on chassis instrument panel ***Includes "Throttle Ready" indicator light on Pump operating panel
30-51-0700	1	Pump Gearbox mounted manual over ride for pump shift E
30-51-1500	1	<i>Power shift PTO - Automatic transmission - for the Hydraulic generator</i>
30-51-1501	1	<i>PTO driveshaft - for the hydraulic pump for the hydraulic generator</i>
30-51-6700	1	<i>FRC Pump Boss Governor/Throttle engine display</i>
30-51-7000	1	<i>Suction side relief V/V, manifold pump</i>
30-51-7500	1	<i>Primer electric vane type 12V with oil tank Waterous</i> Indicator light on panel to show when primer is operating
30-51-8100	1	<i>Heat exchanger included with chassis</i>
30-52-1000	1	Master drain V/V, 12 port
30-52-2000	1	<i>Drain valve for foam system header</i>
30-52-5510	1	<i>Foam system-Hypro FoamPro 2001 Single Tank</i> Foam system is plumbed to both crosslays and the front trashline.
30-52-9100	1	<i>Foam concentrate label at foam tank fill</i>
30-52-9200	1	<i>Foam System Instruction Plates</i>

PART NO	QTY	DESCRIPTION
30-52-9400	1	NFPA Foam System certification test
	1	WATER AND FOAM TANKS
40-11-2100	1	Polypropylene water tank (Imperial gallons)
40-11-2200	1	Water tank capacity certification (tank manufacturer)
40-11-4000	1	Tank capacity 500 Imperial Gallons
40-12-5000	1	Foam cell - 30 Imperial gallon
40-21-0500	1	3" tank to pump connection
40-22-0500	1	2" tank fill connection
40-23-0500	1	1" water level gauge connection
40-23-1000	1	1" foam level gauge connection
40-30-0400	1	3" plug in sump box
40-30-1000	1	Water Fill Box front left corner
40-31-0400	1	Rear dump valve not requested E
40-31-6050	1	Rear fill not requested E
	1	ELECTRICAL
50-11-0300	1	Base electrical system - multiplex E
50-11-0600	1	Warning Light Certification
50-11-0700	1	Low Voltage Electrical system test
50-11-0800	1	Low Voltage Electrical System Documents As required by ULC and NFPA standards
50-11-0900	1	Rocker switch panel with master warning switch ***Rocker switch assignments: MASTER -LIGHT BAR RED -LIGHT BAR CLEAR -FLASHING WARNING -LEFT TELELIGHT -RIGHT TELELIGHT -LEFT SCENE -REAR SCENE -RIGHT SCENE
50-11-1400	1	Federal PA300 100 watt siren
50-11-1620	1	Siren speaker, 100 watt, in front bumper
50-11-2600	1	Siren to be accessible to driver and officer
50-11-6100	1	Whelan FN60QLED LED light bar NFPA The light bar configuration will be as follows from Driver to Officer side: RRRWRR__RBWBRR as requested by Todd Finnie by e-mail on 07.05.2019.
50-11-6501	1	No Rear Directional Light requested
50-11-8001	1	No rear beacons requested
50-12-8520	1	Front LED flashers (pr)-Whelen red/blue LED 600 with integral flasher Mounted in cab grille - Left side to be red and right side to be blue as requested by Todd Finnie by e-mail on 07.05.2019
50-12-8621	1	Rear LED flashers (pr)-Whelen red/blue LED C9 with integral flasher Upper level on rear. The Right side is red and left side is blue as requested by Todd Finnie by e-mail on 07.05.2019
50-12-8710	1	Front side inter lts (pr) - Whelen red LED 600 with integral flasher Mounted in bumper tails
50-12-8810	1	Body side inter lts (pr)-Whelen red LED 600 with integral flasher Mounted in rear part of rear fenders
50-12-8822	2	Body side inter lts (pr)-Whelen red LED C9 with integral flasher Upper level - located each side in front and rear part of side
50-12-8905	1	Add'l body side inter lts (pr)-Whelen red LED 600 with integral flasher Located in space between the front and rear cab doors

PART NO	QTY	DESCRIPTION
50-21-2547	1	FRC Spectra LED 12 Volt telescoping light (ea) - switched in cab SPA530-Q15-SW-SR-NS Located on the front of pump house - one each side Switched in cab Hazard switch (SW) to be wired to the door ajar warning light in cab Steady Rest (SR) included These lights can be managed to shed
50-21-5100	1	Compartment lighting - LED tube lights in each compartment (rollup doors)
50-21-5500	1	Door Ajar warning light Standard 1030436 red warning light (approx 1/2" diameter) mounted in overhead console above drivers seating position. Bilingual warning label in cab to read: "Do Not Move Apparatus when Light is on"
50-21-8001	1	Step lights for body steps - 4" LED Switched when park brake is applied.
50-21-8201	1	Step lights for chassis steps - LED Switched when park brake is applied.
50-21-83AA	1	12" LED lumabars for rear step/platform lighting
50-21-8600	1	LED clearance lts and reflectors
50-21-8800	1	LED intermediate turn signal/clearance/reflector length >30'
50-22-0750	1	Whelen 64 LED CAST 4V tail/brake-turn-backup-warning module (pr) Lower level flashing red warning lights are included in this module.
50-31-40AA	1	6000 watt hydraulic generator Harrison brand - see SOPT #230 Located in front right part of hose bed Control for generator mounted in cab console 20-31-7500 ***Appropriate provisions to route the hydraulic hoses and the wire harness' will be made.***
50-31-6021	1	Whelen C9SL LED Scene lights (pr) - left side Located inboard of upper flashing lights - switched in cab These lights can be managed to shed
50-31-6022	1	Whelen C9SL LED Scene lights (pr) - rear facing Located below the upper flashing lights - switched in cab and when transmission in placed in reverse gear These lights cannot be managed to shed
50-31-6023	1	Whelen C9SL LED Scene lights (pr) - right side Located inboard of upper flashing lights - switched in cab These lights can be managed to shed
50-31-6560	1	Ground lighting (LED Lumabar) - 4 door chassis Switched when park brake is applied.
50-31-6570	1	Ground lighting (LED Lumabar) - side mount body Switched when park brake is applied.
50-35-0500	1	Provisions for installation of customer supplied and installed mobile radio A radio blank shall be provided in the cab console 20-31-7500. Power and ground wires shall be provided - wired thorough the master disconnect and properly labeled.
50-35-0560	1	VHF antenna with base - commercial chassis The customer radio installer has advised that the department uses VHF antenna with frequencies between 151 Mhz to 172 Mhz. Has identified by e-mail on 12.17.2019.

PART NO	QTY	DESCRIPTION
50-99-10AA	1	Hose bed cover lights - 4 x 40" Lumabars Switched when park brake is applied.
51-31-3020	1	120 volt wiring for hydraulic generator Note that Neutral is bonded to chassis ground. Breaker box located in left front compartment unless otherwise specified. Circuits for Cord reel Automatic transfer switch Customer requested additional circuits and/of receptacles by e-mail on 07.05.2019 as follows: Upper portion of R1 compartment, Upper portion of L1 compartment and upper portion of back compartment.
51-31-3100	1	Automatic 110 volt transfer switch Breaker box located in left front compartment unless otherwise specified. Circuits for Three of the 20-51-6200 receptacles Customer requested additional circuits and/of receptacles by e-mail on 07.05.2019 as follows: Upper portion of R1 compartment, Upper portion of L1 compartment and upper portion of back compartment.
51-31-4000	1	Electric cord reel with 200' x 12/3 cable, lighted box mounted side pump house The cord reel will be installed on top of the pump house in the 70-11-5100 open storage. There will be an opening on the right side to allow the junction box to come out and be mounted beside the pump panel access door 70-11-5500. The pump access door will be smaller to create a mounting space and there will be rollers around the opening on the pump house to protect the cable / pump house. As requested by Todd Finnie by e-mail on 07.05.2019.
51-31-4500	1	Dielectric strength test for line voltage system In house dielectric testing will be performed.
	1	BODY
60-10-1400	1	Single axle extruded aluminum body Body configured with full width hose bed.
60-10-4100	1	No "beavertail" rear step supports
60-10-4600	1	Painted fender surround E
60-10-4700	1	Integral aluminum fender trim
60-10-5400	1	Diamondback pumphouse steps
60-10-5430	1	Diamondback 19" rear step
60-10-6000	1	Extruded rub rail
60-11-0300	1	Front left side compartments full height E
60-11-0700	1	Front right side compartments full height E
60-11-1000	1	Rear left side compartments full height E
60-11-1400	1	Rear right side compartments full height E
60-11-2000	2	High side compartment (over 18") each
60-11-3200	1	Full Height Rear compartment
60-11-5500	2	Rollup door - standard height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5520	5	Rollup door - full height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5655	2	Amdor pull straps - Flex - HD - AY-9355-18 - for L2 and R2 Ordered with roll up doors

PART NO	QTY	DESCRIPTION
60-11-5660	5	Amdor pull straps - Flex - Hd - AY-9355-36 - for L1, L3, R1, R3 and B1 Ordered with roll up doors
60-31-4100	1	Extruded aluminum handrails Minimum 2" clearance from handrail to any surface
60-31-5500	1	Steps at rear of body (folding) with LED lights Left side only Maximum height between steps is 18"
60-31-5600	1	Steps and grab handles at front of body next to pump panel Maximum height between steps is 18"
60-31-5800	1	Intermediate step on rear As wide as possible - located over back compartment door Requires LED lighting and delineation.
60-31-6500	1	Compartment matting - plastic interlocking tile
60-31-8003	4	Double SCBA storage tube with door in rear fender (ea) CPI brand Includes cylinder retaining loops Door ajar required
60-31-82AA	2	Adjustable vertical tool board Both in left rear side compartment and they will be adjustable from side to side for fire department adjustment. The unit will have peg board type panel with 1/4" size hole spaced 1-7/16" center to center. As requested by Todd Finnie by e-mail on 07.05.2019.
60-31-8800	3	Sliding tray (ea) - 600 pound capacity ***Hardware requires 3-1/2" of compartment height Reflective stripe is applied on the exposed edge for visibility when the compartment door is open All trays located at compartment floor level. Tray #1 - Left side front compartment Tray #2 - Right side front compartment Tray #3 - Back compartment Customer confirmed locations by e-mail on 05.07.2019
60-31-9600	7	Adjustable shelf (ea) Reflective stripe is applied on the exposed edge for visibility when the compartment door is open. Locations are as follows: Shelf #1 - Left side front compartment - full depth Shelf #2 - Left side compartment over rear wheels - full depth Shelf #3 - Right side front compartment - shallow depth Shelf #4 - Right side compartment over rear wheels - full depth Shelf #5 - Right side rear compartment - shallow depth Shelf #6 - Back compartment - full depth Shelf #7 - Right side front compartment - shallow depth Customer confirmed locations by e-mail on 07.05.2019
60-32-3550	1	Two adjustable hose divider and one fixed to support hose bed covers Hand hold required in end
60-32-7500	1	Hose bed - aluminum Full width
60-33-0000	1	Paint exterior - Imron Elite *** Paint code and colour - single color red to match red on cab

PART NO	QTY	DESCRIPTION
60-33-0200	1	Undercoat vehicle with KROWN rust protection
60-33-0600	1	Chassis wheels not painted Aluminum wheels
60-33-1000	1	Paint pump and plumbing job colour
60-33-1500	1	Buffed finish compartment interior
60-33-2200	1	Lettering - 80 letters up to 3" tall - 3 colour Drawing layout approved August 26
60-33-3000	1	Reflective stripe - 4" white and red 50% of perimeter each side and 25% of perimeter front Striping layout approved August 26
60-33-3310	1	Reflective stripe - red and yellow chevron at rear Minimum 50% of rear vertical surface.
60-33-4600	1	Aluminum cover over crosslays - with end tarps (black) Small tarps with Velcro straps to enclose each end are provided to tie around the bottom horizontal hose rollers.
60-33-5000	1	Aluminum cover over hose bed with end tarps - black E ***Covers will have necessary bracing to minimize flex.*** Door ajar switches required Rear flaps with Velcro straps will be provided on the rear of the cover to tie around footman's loops.
60-40-9000	1	Tube mount for ladders, with rear door Right side with rear access Tube to be enclosed Door ajar required Tube will house the following; 24' two section ladder 80-14-0500 12' roof ladder 80-14-5000 10' attic ladder 80-14-8500 10' pike pole 80-13-2500 8' pike pole 80-13-2200
60-40-9100	1	Smooth aluminum plate door for 60-40-9000 tube for ladders Vertically hinged with "D" handle
60-41-1015	2	Pike Pole tube in ladder tube - integral with 60-40-9000
60-41-1500	1	Attic ladder tube - integral with 60-40-9000
	1	INSTRUMENTATION
70-11-0000	1	Warning Label on Pump Operator's Panel
70-11-0500	1	Side mount instrument panel No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position
70-11-1500	1	Stainless steel instrument panels No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position
70-11-3200	1	Colour coded tags Standard Imperial units, no special colors specified
70-11-4100	1	Stainless steel side panel hood left side
70-11-4500	1	Diamondback grip type panel hood step right side Requires LED lighting and delineation.
70-11-5100	1	Open storage at rear top of pump house Drain holes in floor required

PART NO	QTY	DESCRIPTION
		Plastic interlocking tile on floor required Interior lighting required - switched by park brake.
70-11-5500	1	Right side tread plate pump access door No opening dimension less than 18" Slot required for Primer level viewing
70-11-7500	1	Heat pan-aluminum
70-11-8000	1	Heater in pump compartment Switched on pump operators panel
70-20-1120	2	4-1/2" compound gauge - dual face 0-400 - Thuemling To be within 8" of each other - edge to edge
70-20-2130	9	2-1/2" pressure gauge - dual face 0-400 - Thuemling Combination control rod assembly/gauge
70-20-2500	1	Primer control
70-20-3200	1	FRC Pump Boss Governor Control Throttle can be no lower than 42" and no higher than 72" from operator's standing position.
70-20-3500	1	Electric water level gauge on pump panel, Class One
70-20-6500	1	Test gauge panel Mount below the compound gauges for proper draining
70-20-7500	1	Heat exchanger control valve
70-21-1500	1	Electric Foam Level gauge on pump panel, Class One
70-21-2100	1	PTO Hourmeter Included with the hydraulic generator control module.
70-21-5500	1	Panel readout for Battery Conditioner Located on left side pump panel
	1	ACCESSORIES
80-13-2200	1	Pike pole, fibreglass handle - 8' long Flamefighter PP08 Tube mounted
80-13-2500	1	Pike pole, fibreglass handle - 10' long Flamefighter PP10 Tube mounted
80-14-0500	1	24' 2 section extension ladder PEL 24 Tube mounted
80-14-5000	1	12' aluminum roof ladder PRL-12 Tube mounted
80-14-8500	1	10' aluminum folding attic ladder FL-10 Tube mounted
80-18-0500	1	SCBA bracket with strap - compt mount - for Drivers SCBA ship loose Bracket will be shipped loose as requested by Todd Finnie by e-mail on 05.07.2019.
80-18-0600	4	SCBA brkt w/strap - ZICO ULLH - crew cab mount Mounted in cab SCBA seats
80-19-0500	2	Large folding wheel chock - aluminum (ea) not mounted
80-19-0600	2	Horizontal bracket for folding wheel chock (ea) Mounted under left side front compartment just forward of rear wheels

