



Shop Order

ELG, Local Government
 Marysville Place
 20 McGloin Street
 Fredericton, NB E3A 5TA

Coles Island Fire Department
 Province of NB

| | |
|---|--|
| Sales Rep: Ryan Stacey Metalfab Ltd. | Terms: Chassis, body and Equipment Net 30 days |
| Drawing #: FT-11679 | |
| Est. Delivery Date: / / | |
| Customer PO #: P100400624 | Penalty: |
| Customer #: 457 | |
| QPF #: | |

Exp. Date: 01/26/2024
Quote No: G-PNB 2024 Fast Resp-0022
Job/Order No: 23264
BODY: 00-10-36 Metalfab Fast Response - 05/13

07/15/2025

| PART NO | QTY | DESCRIPTION |
|---|----------|--|
| == Metalfab Fast Response - 05/13 - 0.000 == | | |
| Change Order G | | |
| 00-10-0500 | 1 | Metalfab Minipumper |
| 00-20-1000 | 1 | Company Profile |
| 00-20-1501 | 1 | Extended Body Warranty - one year on site Warranty issues will be resolved FOB Fire Department for first year |
| 00-20-1550 | 1 | Metalfab Limited Ten (10) Year Paint and Corrosion Warranty |
| 00-20-1700 | 1 | Hale Pump Warranty - 5 years |
| 00-20-1800 | 1 | Polypropylene Water Tank Warranty |
| 00-20-2000 | 1 | Plant Visits - unlimited at customer expense |
| 00-20-3500 | 1 | Certification for Fusion Welding of Steel and Aluminum |
| 00-20-4000 | 1 | Quality System registered to ISO 9001:2015 |
| 00-20-4500 | 1 | Fire Apparatus Manufacturers' Association Membership |
| GENERAL INFORMATION | | |
| 10-11-0000 | 1 | Intent |
| 10-11-0105 | 1 | Vehicle Data Recorder not available from Ford The standard seat belt warning from Ford will be on the OEM seats. |
| 10-11-1101 | 1 | ULC 515 2024 Edition Compliance |
| 10-11-1500 | 1 | ULC Testing - Intial Attack Fire Fighting Apparatus - Imperial units of measure |
| 10-11-2100 | 1 | Maximum length not specified |
| 10-11-2200 | 1 | Maximum height not specified |
| 10-11-2300 | 1 | Overall length is less than 30' |

| PART NO | QTY | DESCRIPTION |
|----------------------------|------------|--|
| 10-11-2500 | 1 | General Construction |
| 10-11-3000 | 1 | Manuals - two copies and one (1) Digital ***Two copies of manuals are required and one (1) digital copy |
| 10-11-3600 | 1 | Delivery - FOB Fire Department Minimum of 8 hours of training shall be provided and one (1) video presentation to be used for future training |
| 10-11-4200 | 1 | Payment Terms - Chassis and Body Net 30 days |
| 10-20-1250 | 1 | Hose bed capacity - standard Mini Pumper The hose load for a standard Mini Pumper is as follows; 300' of 2-1/2" double jacket hose 400' of 1-3/4" double jacket hose |
| 10-20-2250 | 1 | Equipment carrying capacity - standard ULC/NFPA Mini Pumper This vehicle is designed to carry the standard ULC miscellaneous equipment load of 1500 pounds for a Mini Pumper with a GVW of 15,001 to 20,000 pounds. |
| CHASSIS INFORMATION | | |
| 20-11-1010 | 1 | Chassis supplied by Metalfab - Ford Super Duty F-550 XL 4WD Crew Cab 203" Wheelbase 84" Cab to axle 19,500 lb GVWR 6,500 lb front axle 14,706 lb rear axle V-8 Diesel 6.7 litre engine 300 hp @ 2600 rpm 825 lb-ft torque @ 2000 rpm 10-Speed TorqShift automatic transmission 410 amp dual alternators Single fuel tank behind rear axle Color is Race Red Power window regulators Rubber floor Steel wheels with stainless trim Power Mirrors |
| 20-11-10AA | 1 | Chassis Dealer - Downey Ford |
| 20-11-1500 | 1 | 2013 Emission chassis modifications |
| 20-11-1700 | 1 | Chassis Motor Vehicle Inspection required - NB Chassis is provided with a New Brunswick Motor Vehicle Inspection dated the month of delivery. |
| 20-21-0500 | 1 | Fluid capacity plate |
| 20-21-0600 | 1 | Pumping test plate |
| 20-21-1030 | 1 | Maximum riders sign - 5 persons |
| 20-21-1510 | 1 | Seat belt warning labels - 4 door chassis |
| 20-21-1520 | 3 | Helmet warning label - do not wear helmet |
| 20-21-1530 | 1 | Tire Pressure Indicators - Single Axle |
| 20-21-1600 | 1 | Apparatus Information Label An information label is provided in the chassis cab, visible to the driver, stating: "When manufactured, this vehicle was: ** m high ** m long ** kg GVW Changes in height since the apparatus was manufactured shall be noted on this plate by the Fire Department" |

| PART NO | QTY | DESCRIPTION |
|-------------------|------------|--|
| 20-21-2000 | 1 | Non removable key There will be a chain attached to the key to meet ULC |
| 20-21-2500 | 1 | Shifter lock not required |
| 20-21-3500 | 1 | Rear step warning label |
| 20-21-3800 | 1 | Front mudflaps |
| 20-21-4000 | 1 | Rear mudflaps - Metalfab Logo |
| 20-31-0100 | 1 | Fuel tank or step covers not required |
| 20-31-0200 | 1 | Fuel fill label -Ultra Low Sulfur Diesel only Include a label for the DEF fill as well. |
| 20-31-1900 | 1 | Chassis cab painted Race Red by OEM Ford Motor Co. |
| 20-31-7500 | 1 | Console in cab Install switch panel (50-11-0900), siren (50-11-1470), Traffic light (50-11-7600), provisions for Customer's radios (50-35-0500), Pump shift indicator lights, and door ajar light (50-21-5600) in console. Mount 20-52-4000 rear view monitor at RS front of console. 12-volt power point (20-90-1500) and USB power point (20-90-1600) shall also be located on console. Storage area with hinged cover and lift and turn latch provided at rear of console. Gray Zolatone finish |
| 20-31-7588 | 1 | Remove center section of front cab seat for room for console (Ford and Dodge) Do not ship loose with completed truck, send to tarp shed |
| 20-41-0600 | 1 | Intake air shutoff for engine not requested |
| 20-41-1520 | 1 | Extend exhaust pipe - RS rear of rear wheels Engineering to specify exhaust pipe material as required by the chassis manufacturer. Engineering to sign off on the exhaust configuration to make sure it meets the chassis manufacturer's emission specifications. |
| 20-41-1801 | 1 | Battery boost terminals not required - batteries accessible |
| 20-41-2000 | 1 | Chassis batteries remain in OEM location |
| 20-41-2565 | 1 | Fuel fill guard in rear fender well Single Fuel fill guard (as provided by Ford) only due to single tank |
| 20-41-2600 | 1 | Chassis fuel tank remains in OEM location |
| 20-41-5000 | 1 | Rear Tow Hooks - under body *** Flat bar tow hooks under rear step (2) |
| 20-41-5200 | 1 | Rear trailer receiver - Class III/IV and 7-pin trailer connection There will be a 7-pin trailer connection wired to industry standard Capacity label installed close to receiver Maximum trailer weight - 10,000 lb Maximum tongue weight - 1,000 lb |
| 20-51-05AA | 1 | Master disconnect switch - push button switch Push button switch on cab console Disconnects Metalfab installed components only as required by Ford Body Builder Advisory Service |
| 20-51-2600 | 1 | Back up alarm |

| PART NO | QTY | DESCRIPTION |
|--------------------------|------------|--|
| 20-51-3100 | 1 | Air inlet not requested |
| 20-51-6200 | 3 | 120 volt 20 A shore line connection in chassis cab and body Standard 5-20R duplex receptacle in chassis cab, not fused to be on back wall of chassis, 12" off the floor as per ULC for battery conditioner One each mounted high in right rear compartment and front left compartment |
| 20-51-6500 | 1 | Kussmaul Autocharge 1000 battery conditioner w/battery saver Will be installed under rear seat |
| 20-51-7101 | 1 | Electric System Management - VMUX |
| 20-51-7500 | 1 | Super Auto eject for 120 v - 20 A with sealed enclosure Located driver side pump panel |
| 20-51-8510 | 1 | Engine compartment lighting LED lumabar One required to light up engine compartment Powered when transmission is in park and ignition is on |
| 20-51-8600 | 1 | Air intake ember separator Installed by Metalfab |
| 20-51-9002 | 1 | Air horns not requested |
| 20-52-1100 | 1 | Red/white dome light (ea) - surface mount Switched on light head - located in rear cab crew area |
| 20-52-4000 | 1 | Rear View Camera system Rearview Systems STM5600 with 5.6" colour monitor in cab Mount monitor on top of the dash similar to Long Reach |
| 20-60-0400 | 1 | Chassis wheelbase does not change |
| 20-90-1500 | 1 | 12 volt power point Located in 20-31-7500 console Socket type receptacle (Metalfab p/n 1030961) Switched through 20-51-05AA master disconnect |
| 20-90-1600 | 1 | Kussmaul Dual USB charging socket Located in 20-31-7500 console Kussmaul model #091-219-5 (Metalfab p/n 1521659) Switched through 20-51-05AA master disconnect |
| 20-99-05AA | 1 | Running boards for Ford F-550 Crew cab 4x4 Stainless tube type steps provided by Metalfab (from Speedy) |
| PUMP AND PLUMBING | | |
| 30-11-3800 | 1 | Hale DSD midship pump - 1050 IGPM |
| 30-15-0304 | 1 | Plumbing - non manifold pump SM SS |
| 30-20-0500 | 1 | Valves and controls - side mount panel |
| 30-20-1002 | 1 | Akron valves specified |
| 30-20-1620 | 1 | Piping stainless steel - non manifold Pumper |
| 30-20-1700 | 1 | 1-1/2" thread specifications - Storz Red Head Storz adapters |
| 30-20-1800 | 1 | 2-1/2" thread specifications - Storz Red Head Storz adapters |

| PART NO | QTY | DESCRIPTION |
|-----------------------------|------------|---|
| 30-20-2000 | 1 | Piping hydrostatic test |
| 30-20-2510 | 1 | Anodes in suction and discharge piping - non manifold pump Install one anode on discharge side of pump, one anode on suction side of pump - do not use teflon tape or thread sealant. Paint flange silver and mask brass anode before painting for visibility. |
| 30-21-5520 | 1 | Tank to Pump SS 3" w/ check valve non manifold pump 3" Piping, valve and check valve |
| 30-22-0520 | 1 | Tank Fill valve 2" SS |
| 30-31-4020 | 1 | Suction - 6" not gated each side SS non manifold pump 6" header |
| 30-32-7550 | 1 | Suction - 2-1/2" left side SS, bleeder, non manifold pump |
| 30-32-8050 | 1 | Suction - 2-1/2" right side SS, bleeder, non manifold pump |
| 30-40-2006 | 1 | 4" right discharge, SS, plumbed 3", bleeder, non manifold pump |
| 30-41-2040 | 1 | 2-1/2" RS discharge SS, bleeder, non manifold pump |
| 30-41-2540 | 2 | 2-1/2" LS discharge SS, bleeder, non manifold pump |
| 30-43-1520 | 2 | 2-1/2" rear discharge SS, plumbed 2-1/2", bleeder One on each side of body at rear. Plumbed through compartments |
| 30-44-0520 | 2 | 1-1/2" crosslay (each) SS, 2" valve, bleeder Both crosslays to be foam capable Capacity to be 200' of 1.75" hose in each crosslay |
| 30-51-0500 | 1 | Pump shift-Midship air ***Includes "Pump Engaged" and "OK to Pump" indicator lights in cab ***Includes "Throttle Ready" indicator light on Pump operating panel |
| 30-51-0520 | 1 | 12-Volt air compressor and air tank for chassis - for use with pump shift Locate ahead of tank |
| 30-51-6810 | 1 | FRC InControl Governor/Throttle engine display with buttons To be compatible with Ford chassis |
| 30-51-6840 | 1 | Ford Translator Module for FRC InControl to J1939 |
| 30-51-7002 | 1 | Suction side relief V/V, non manifold pump |
| 30-51-7702 | 1 | Primer Hale oil less ESP with oil tank - for Hale DSD Indicator light on panel to show when primer is operating Include a disconnect switch to cut power to primer in the event of a solenoid failure location of switch by Metalfab |
| 30-52-1000 | 1 | Master drain V/V, 12 port |
| 30-52-2000 | 1 | Drain valve for foam system header |
| 30-52-4015 | 1 | Foam System - Hypro FoamPro 1600 Foam is plumbed to both 1-1/2" crosslays. |
| 30-52-9100 | 1 | Foam concentrate label at foam tank fill |
| 30-52-9200 | 1 | Foam System Instruction Plates |
| 30-52-9400 | 1 | NFPA Foam System certification test |
| WATER AND FOAM TANKS | | |
| 40-11-2100 | 1 | Polypropylene water tank (Imperial gallons) |
| 40-11-2200 | 1 | Water tank capacity certification (tank manufacturer) |
| 40-11-2500 | 1 | Tank capacity 200 Imperial Gallons Metalfab will build tank after body has been completed and weighed to get as close |

| PART NO | QTY | DESCRIPTION |
|-------------------|------------|---|
| | | to 200 IG as possible. Final capacity will be determined by dry weight of chassis and cab, final body design and accessories chosen. |
| 40-12-4500 | 1 | Foam cell - 10 Imperial gallon |
| 40-21-0500 | 1 | 3" tank to pump connection |
| 40-22-0500 | 1 | 2" tank fill connection |
| 40-23-0500 | 1 | 1" water level gauge connection |
| 40-30-0400 | 1 | 3" plug in sump box |
| 40-31-6050 | 1 | Rear fill not requested |
| ELECTRICAL | | |
| 50-11-0300 | 1 | Base electrical system - multiplex |
| 50-11-0600 | 1 | Warning Light Certification |
| 50-11-0700 | 1 | Low Voltage Electrical system test |
| 50-11-0800 | 1 | Low Voltage Electrical System Documents As required by ULC and NFPA standards |
| 50-11-0900 | 1 | Rocker switch panel with master warning switch ***Rocker switch assignments: E-MASTER LIGHT BAR RED LIGHT BAR WHT FLASHING WARNING REAR SCENE HIGH IDLE |
| 50-11-1470 | 1 | Whelen 295SLSC1 100 Watt / 200 Watt siren - with removable microphone Mount in cab console |
| 50-11-1630 | 1 | Siren speaker, 200 watt, in front bumper Mount in front bumper |
| 50-11-5812 | 1 | Federal Allegiant NFPA LED light bar - red/white 1571350 BAR, LIGHT ALGT53-NFPA2 REF#1738088990 53" White lights disabled when park brake is set |
| 50-11-7600 | 1 | Rear LED Federal Signal Master warning lights SL8S SL8S-A-50 31.6" model - (8) Amber light heads, A-A-A-A-A-A-A, SignalMaster Economy Controller, 50-ft cable |
| 50-11-8001 | 1 | Rear beacons not required |
| 50-12-5028 | 1 | Front LED flashers (pr)-red Federal QL43 |
| 50-12-5120 | 1 | Rear LED flashers (pr)-red Federal QL97XF-R - Upper level |
| 50-12-5218 | 1 | Front side inter lts (pr)-red LED Federal QL43 |
| 50-12-5318 | 1 | Body side inter lts (pr)-red LED Federal QL43 |
| 50-12-5320 | 1 | Body side warning lights (pr)-red LED Federal QL97XF-R Upper level on sides of body near rear corner. |
| 50-21-2561 | 2 | FRC telescoping Evolution II LED 12V flood (ea) Wired to the "Do not move apparatus" light in the cab Switched on PUMP PANEL |

| PART NO | QTY | DESCRIPTION |
|-------------------|------------|--|
| 50-21-5100 | 1 | Compartment lighting - LED tube lights in each compartment (rollup doors) |
| 50-21-5500 | 1 | Door Ajar warning light Bilingual warning label in cab to read: "Do Not Move Apparatus when Light is on" Locate in cab console |
| 50-21-8001 | 1 | Step lights for body steps - 4" LED Switched when transmission is placed in park and ignition on. |
| 50-21-8201 | 1 | Step lights for chassis steps - LED Luma bar Switched when transmission is placed in park and ignition on. |
| 50-21-8600 | 1 | LED clearance lts and reflectors |
| 50-22-0800 | 1 | Federal 4 QuadraFlare LED tail/brake-turn-backup-warning module (pr) |
| 50-31-6013 | 1 | Scene lights (pr) - Whelen M6ZC LED - rear facing Switched in cab and when vehicle is in reverse, and not wired to shed |
| 50-31-6560 | 1 | Ground lighting (LED Lumabar) - 4 door chassis Switched when transmission is placed in park and ignition on |
| 50-31-6570 | 1 | Ground lighting (LED Lumabar) - side mount body Switched when transmission is placed in park and ignition on |
| 50-35-0500 | 2 | Provision for customer supplied and installed mobile radio Power and ground provided at console for customer radios. Metalfab will supply suitable faceplates for customer radios if this information is provided, otherwise blank panels are provided. Provided one faceplate mount for a Motorola APX 4500 for customer supplied and installed radio in place of blank panel. |
| 50-35-0560 | 1 | VHF antenna with base - commercial chassis |
| 50-35-0590 | 1 | Cellular/TMR antenna with base - commercial chassis |
| | | BODY |
| 60-10-1000 | 1 | Mini Pumper aluminum body |
| 60-10-4100 | 1 | No "beavertail" rear step supports |
| 60-10-4500 | 1 | Aluminum tread plate fender surround - single axle |
| 60-10-4700 | 1 | Integral aluminum fender trim |
| 60-10-5450 | 1 | Diamondback 10" rear step |
| 60-10-6500 | 1 | Bolt on extruded aluminum rub rail |
| 60-11-0300 | 1 | Front left side compartments full height |
| 60-11-0700 | 1 | Front right side compartments full height |
| 60-11-1000 | 1 | Rear left side compartments full height |
| 60-11-1400 | 1 | Rear right side compartments full height |
| 60-11-2000 | 2 | High side compartment (over 18") each |
| 60-11-3200 | 1 | Rear compartment |
| 60-11-5500 | 2 | Rollup door - standard height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point |
| 60-11-5520 | 5 | Rollup door - full height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point |

| PART NO | QTY | DESCRIPTION |
|-------------------|------------|---|
| 60-31-4100 | 1 | Extruded aluminum handrails Minimum 2" clearance from handrail to any surface |
| 60-31-5500 | 1 | Steps at rear of body (folding) with LED lights Maximum height between steps is 18" Three (3) per side Switched when transmission is placed in park and ignition on |
| 60-31-5600 | 1 | Steps and grab handles at front of body next to pump panel To access top of body Maximum height between steps is 18" Switched when transmission is placed in park and ignition on |
| 60-31-6500 | 1 | Compartment matting - black plastic interlocking tile |
| 60-31-9600 | 9 | Adjustable shelf (ea) White reflective stripe is applied on the exposed edge for visibility when the compartment door is open Location of shelves, all full depth: Shelf #1 - L1 Shelf #2 - L1 Shelf #3 - L1 Shelf #4 - L2 Shelf #5 - R1 Shelf #6 - R1 Shelf #7 - R3 Shelf #8 - R3 Shelf #9 - R3 All shelves to be adjusted to be equally spaced vertically in the compartment |
| 60-32-3560 | 1 | Three adjustable hose divider (each) Hand hold required in end |
| 60-32-7500 | 1 | Hose bed - aluminum |
| 60-33-0000 | 1 | Paint exterior - Imron Elite *** Paint code and colour red to match body |
| 60-33-0200 | 1 | Undercoat vehicle with KROWN rust protection |
| 60-33-0600 | 1 | Chassis wheels not painted - aluminum wheels |
| 60-33-1000 | 1 | Paint pump and plumbing job colour |
| 60-33-1600 | 1 | Special paint compartment interior - gray zolatone |
| 60-33-2200 | 1 | Lettering - 80 letters up to 3" tall - 3 colour Lettering layout drawing approved by customer May 5-25 |
| 60-33-3000 | 1 | Reflective stripe - 4" white 50% of perimeter each side and 25% of perimeter front Striping layout drawing approved by customer May 5-25 |
| 60-33-3310 | 1 | Reflective stripe - red and yellow chevron at rear Minimum 50% of rear vertical surface. 3M printed Scotchlite material Roll up door does not have Chevron applied |
| 60-33-3500 | 1 | Tarp over hose bed - black |

| PART NO | QTY | DESCRIPTION |
|------------------------|------------|--|
| 60-33-3600 | 1 | Reflective stripe - inside entry doors 96 square inches minimum inside each cab entry door |
| 60-33-4600 | 1 | Aluminum cover over crosslays - with end tarps (black) Installed with hinge to front of unit and stop with rubber bumpers. |
| 60-40-5000 | 3 | 6" Hose tray - top mount (ea) Located top left of body, configured to pull hoses out from rear and secured by velcro straps. Sized to fit three 6" x 8' long suction hose 80-11-50AA |
| 60-40-9000 | 1 | Tray mount for ladder Located top right of body in slide out tray with hold down. Sized to fit 80-14-05AA 12' Fresno attic extension ladder |
| 60-41-1000 | 1 | Pike Pole storage Located adjacent or integral with ladder tray 60-40-9000. For storage of the 8' pike pole 80-13-2200 |
| INSTRUMENTATION | | |
| 70-11-0000 | 1 | Warning Label on Pump Operator's Panel |
| 70-11-0500 | 1 | Side mount instrument panel No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position |
| 70-11-1500 | 1 | Stainless steel instrument panels No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position |
| 70-11-3200 | 1 | Colour coded tags |
| 70-11-4002 | 1 | Stainless steel side panel hood right side |
| 70-11-4102 | 1 | Stainless steel side panel hood left side |
| 70-11-5000 | 1 | Standard cover over rear top of pump house - no storage |
| 70-11-5500 | 1 | Right side tread plate pump access door No opening dimension less than 18" Slot required for Primer level viewing |
| 70-11-7500 | 1 | Heat pan-aluminum |
| 70-11-8000 | 1 | Heater in pump compartment Switch for heater is located on the left side pump operator's panel |
| 70-20-1120 | 2 | 4-1/2" compound gauge - dual face 0-400 Thuemling brand |
| 70-20-2130 | 8 | 2-1/2" pressure gauge - dual face 0-400 - Thuemling brand Gauge to be no more than 6" from edge of the gauge to the center of the control. |
| 70-20-2500 | 1 | Primer control |
| 70-20-3300 | 1 | FRC InControl Governor Control Throttle can be no lower than 42" and no higher than 72" from operator's standing position. |
| 70-20-3510 | 1 | Electric water level gauge on LS and RS pump panels, Class One 1530705 |
| 70-20-6500 | 1 | Test gauge panel |

| PART NO | QTY | DESCRIPTION |
|--------------------|------------|--|
| 70-21-1600 | 1 | <i>Electric Foam Level gauge not required</i> 1530702 |
| 70-21-5500 | 1 | <i>Panel readout for Battery Conditioner</i> To be installed on left side pump panel |
| ACCESSORIES | | |
| 80-11-50AA | 3 | <i>6" x 8' lightweight suction hose</i> Tray mounted on top of body 1510450 |
| 80-12-2500 | 1 | <i>6" barrel strainer</i> Shipped loose |
| 80-13-1000 | 3 | <i>Hose wrenches (double) with holder</i> Mount one on rear wall of body, and one each on front wall of LS and RS front compartments |
| 80-13-1500 | 1 | <i>Bar with bracket</i> Mounted in standard location under back compartment door opening above rear step. |
| 80-13-2200 | 1 | <i>Pike pole, fibreglass handle - 8' long</i> Mounted on top of body |
| 80-14-05AA | 1 | <i>12' Fresno Attic Extension Ladder</i> Tray mounted on top of body Alco Lite AEL-12 |
| 80-18-0500 | 4 | <i>SCBA bracket with strap - compt mount</i> Mount in RS compartment over rear wheels on horizontal unistruts to allow adjustment side to side |
| 80-19-0500 | 2 | <i>Large folding wheel chock - aluminum (ea) not mounted</i> Shipped loose with unit |
| 80-19-0600 | 2 | <i>Horizontal bracket for folding wheel chock (ea)</i> Mount under body ahead of the rear wheels on the left side |
| 80-99-05AA | 1 | <i>Supply and install Rescue Tool Carousel</i> Install a Zico QM-MEH-1rescue tool carousel to floor of LS rear compartment - floor to be reinforced to distribute the weight. |