



Shop Order

The Village of Southern Victoria
 Dan Dionne CAO
 1131 West Riverside Drive
 Perth-Andover, NB E7H 5G5
 dan@vilsv.ca

The Village of Southern Victoria
 Dan Dionne CAO
 1131 West Riverside Drive
 Perth-Andover, NB E7H 5G5
 dan@vilsv.ca

Sales Rep: Ryan A. Stacey Business Development Manager	Terms: Chassis Net 10 Days Body & Equipment COD
Drawing #: FT-11684	
Est. Delivery Date: / /	
Customer PO #:	Penalty:
Customer #:	None
QPF #:	

Exp. Date: 12/02/2023
Quote No: RPENB-0016
Job/Order No: 23220
BODY: 00-10-15 Metalfab Pumper - ULC 05/13

11/27/2025

PART NO	QTY	DESCRIPTION
== Metalfab Pumper - ULC 05/13 - 0.000 ==		
Change Order G		
00-05-0010	1	Dealer - Metalfab
00-10-1500	1	Metalfab Pumper
00-20-0500	1	List of References not provided
00-20-1000	1	Company Profile
00-20-1500	1	Standard Body Warranty
00-20-1550	1	Metalfab Limited Ten (10) Year Paint and Corrosion Warranty
00-20-1600	1	Waterous Pump Warranty - 5 years
00-20-1800	1	Polypropylene Tank Lifetime Warranty
00-20-2000	1	Plant Visits - unlimited at customer expense
00-20-3000	1	No Bonding Required
00-20-3500	1	Certification for Fusion Welding of Steel and Aluminum
00-20-4000	1	Quality System registered to ISO 9001:2015
00-20-4500	1	Fire Apparatus Manufacturers' Association Membership
GENERAL INFORMATION		
10-11-0000	1	Intent
10-11-0110	1	Vehicle data recorder included with chassis
10-11-1100	1	ULC S515-13 Compliance
10-11-1500	1	ULC Testing - Pumper - Imperial units of measure
10-11-2100	1	Maximum length not specified
10-11-2200	1	Maximum height not specified
10-11-2400	1	Overall length is 30' or more
10-11-2500	1	General Construction

PART NO	QTY	DESCRIPTION
10-11-3000	1	Manuals - two copies ***Two copies of chassis manuals are required.
10-11-3600	1	Delivery - FOB Fire Department
10-11-4000	1	Payment Terms - Chassis Net 10 days, Balance COD
10-20-1400	1	Hose capacity exceeding ULC/NFPA requirements Add 1000 pounds for additional hose to be carried over the standard ULC requirements Hose bed capacities as follows: 1-1/2" speedlays - 150' each 2-1/2" crosslay - 150' 1-1/2" front trashline - 200' Main hose bed - 1200' 4" LDH and 600' 2-1/2"
10-20-2000	1	Equipment carrying capacity - standard ULC Pumper CHASSIS INFORMATION
20-11-1060	1	Chassis supplied by Metalfab - International HV607 4 door 2025 International HV607 4 door 14,000 FA, 30,000 RA, 44,000 GVW 288" WB, 177" CA, 100" AF Configured for Diamond Logic with three RPMs, switch panels, indicator light panel. Single air horn with lanyard and officer push button L9-360 HP @ 2200 RPM, 1150 torque @ 1200 RPM 3000EVS automatic transmission with LH and RH PTO openings 70 gallon fuel tank, 7 gallon DEF tank 5 person cab with air ride driver, SCBA officer and crew AC, red seat belts, power windows, exterior visor, aluminum wheels with nut covers and hub caps 209WL two tone paint, 9219 White over 2303 Red Stability control, XDN2 rear tires Driveline is SPL170, pump will have 1710 yokes and will be adapted to this driveline
20-11-1500	1	2013 Emission chassis modifications
20-11-1700	1	Chassis Motor Vehicle Inspection required - NB
20-21-0500	1	Fluid capacity plate
20-21-0600	1	Pumping test plate
20-21-1030	1	Maximum riders sign - 5 persons
20-21-1510	1	Seat belt warning labels - 4 door chassis
20-21-1560	1	LED Tire Pressure Indicators - Single Axle
20-21-1600	1	Apparatus Information Label An information label is provided in the chassis cab, visible to the driver, stating: "When manufactured, this vehicle was: ** m high ** m long ** kg GVW Changes in height since the apparatus was manufactured shall be noted on this plate by the Fire Department"
20-21-2000	1	Non removable key
20-21-2500	1	Shifter lock not required
20-21-3500	1	Rear step warning label
20-21-3800	1	Front mudflaps by Metalfab

PART NO	QTY	DESCRIPTION
20-21-4000	1	Rear mudflaps - Metalfab Logo
20-21-4500	1	Transportation Safety Kit Basic First Aid Kit Safety Triangle 5 pound Fire Extinguisher
20-31-0200	1	Fuel fill label -Ultra Low Sulfur Diesel only
20-31-1100	1	Alum tread fuel tank covers, diamond grip steps, Conv - 4 dr
20-31-1900	1	Chassis cab not painted
20-31-4710	1	Extend front bumper, gravshld with hosewell, cover, and D handle latch Hosewell to have a capacity of 200' x 1-1/2" hose plus a nozzle D handle latch and gas strut provided
20-31-7500	1	Console in cab Install siren, TACTL5 control and pump shift in console. 20-90-1600 USB charging socket provided on console. 20-41-5500 On Spot switch on cab console next to driver. Storage area with hinged cover and lift and turn latch provided at rear of console. Gray zolatone finish with black powder coated panels, two radio mounting panels for customer supplied radios. *** Note that console is not to extend back any further than the kick plate on the back of the front seats *** Provide a drawing for customer approval prior to fabrication
20-41-0600	1	Intake air shutoff for engine not required
20-41-0900	1	Auxiliary braking system disabled when pumping
20-41-1100	1	Transmission programming - Allison WT ***Includes "Pump Engaged" light next to pump shift on chassis instrument panel.
20-41-1500	1	Extend exhaust pipe - RS front of rear wheels Engineering to specify exhaust pipe material as required by the chassis manufacturer. Engineering to sign off on the exhaust configuration to make sure it meets the chassis manufacturer's emission specifications.
20-41-1900	1	Battery boost terminals with chassis Positive terminal only included with chassis in the LS step area Metalfab to install the negative terminal in the LS step area
20-41-2000	1	Chassis batteries remain in OEM location
20-41-2510	1	Fuel fill at step fuel tank under cab
20-41-2600	1	Chassis fuel tank remains in OEM location
20-41-5000	1	Rear Tow Hooks - under body *** Flat bar tow hooks under rear step (2)
20-41-5500	1	ON SPOT Automatic traction chains Install switch on cab console 20-31-7500
20-51-0700	1	Master Battery Disconnect included with chassis
20-51-2500	1	Back up alarm included with chassis
20-51-3400	1	Protection valve installed for air operated accessories
20-51-4000	1	Auto eject for air inlet - LS Mount on LS cab step trim between front and rear doors

PART NO	QTY	DESCRIPTION
20-51-6500	1	Kussmaul Autocharge 1000 battery conditioner w/battery saver
20-51-7101	1	Electric System Management through Diamond Logic
20-51-7500	1	Super Auto eject for 120 v - 20 A with sealed enclosure Mount on LS cab step trim between front and rear doors
20-51-8510	1	Engine compartment lights LED LED light in engine compartment - single light to light up complete engine compartment. Switched at light and powered from the master disconnect switch
20-51-9100	1	Air horns on hood, lanyard control plus officer's button Controls provided with chassis, Metalfab supplies and installs air horns.
20-52-3000	1	Chassis steering wheel lined up by others Required for all chassis except Freightliner, Sterling, Spartan
20-52-4009	1	Pro-Vision camera system - 4 cameras - front, right, left and rear - with VDR Mount the monitor on top of the cab dash unless otherwise specified. Rear view camera active when vehicle is in reverse RS and LS cameras active when corresponding turn signal activated
20-52-40AA	1	Pro Vision weatherproof monitor on pump panel Install on pump panel to display front, rear and RS cameras
20-60-0400	1	Chassis wheelbase does not change
20-90-1600	1	Kussmaul Dual USB charging socket Installed on cab console, dual USB-A Note that a USB-A/USB-C socket is provided with the chassis as well Powered from master disconnect switch
PUMP AND PLUMBING		
30-12-4000	1	Mechanical seals for Waterous pumps
30-12-6000	1	Waterous CSU single stage 1250 IGPM Driveline is SPL170, pump will have 1710 yokes and will be adapted to this driveline
30-15-0204	1	Plumbing - Waterous manifold pump SM SS
30-20-0500	1	Valves and controls - side mount panel
30-20-1002	1	Akron valves specified
30-20-1600	1	Piping stainless steel - general
30-20-1700	1	1-1/2" thread specifications NPSH
30-20-1800	1	2-1/2" thread specifications BCT 3x8
30-20-2000	1	Piping hydrostatic test
30-20-2500	1	Anodes in suction and discharge piping Install one anode on discharge side of pump, one anode on suction side of pump - do not use teflon tape or thread sealant. Paint flange silver and mask brass anode before painting for visibility.
30-21-9515	1	Tank to Pump 4" Ball valve SS, electric control with check valve manifold pump
30-22-0520	1	Tank Fill valve 2" SS
30-31-4010	1	Suction - 6" each side manifold pump
30-31-7210	2	Waterous master intake suction valve - electric control Left side and Right side large suction

PART NO	QTY	DESCRIPTION
		Include access to manual over ride
30-31-72AA	1	Speed wrench for Waterous manual over ride, mounted Mount with PAC brackets (1003-HD-Y) to inside of pump compartment door
30-32-7535	1	Suction - 2-1/2" left side SS, bleeder, Waterous manifold pump
30-32-8035	1	Suction - 2-1/2" right side SS, bleeder, Waterous manifold pump
30-40-2025	1	4" right discharge SS, plumbed 3", Waterous manifold pump
30-41-2025	1	2-1/2" RS discharge SS, bleeder, Waterous manifold pump
30-41-2525	2	2-1/2" LS discharge SS, bleeder, Waterous manifold pump
30-43-1520	1	2-1/2" rear discharge SS, plumbed 2-1/2", bleeder Right side rear under hose bed
30-44-0720	2	1-1/2" speedlay (each) front of pumphouse SS, plumbed 2" Locate at front of pump house
30-44-07AA	2	Spare speedlay tray
30-44-1000	1	1-1/2" front trash line, plumbed 2", hosewell
30-44-3520	1	2-1/2" crosslay SS, plumbed 2-1/2", bleeder
30-44-65AA	1	Piping for monitor with separate water and foam valves Two valves and two controls - one water only, one foam/CAFS capable
30-51-0500	1	Pump shift-Midship air ***Includes "Pump Engaged" and "OK to Pump" indicator lights on chassis instrument panel ***Includes "Throttle Ready" indicator light on Pump operating panel
30-51-0700	1	Pump Gearbox mounted manual over ride for pump shift
30-51-1500	1	Power shift PTO - Automatic transmission
30-51-1501	1	PTO driveshaft
30-51-6800	1	FRC InControl Governor/Throttle engine display with throttle knob
30-51-7000	2	Suction side relief V/V, manifold pump
30-51-7720	1	Additional air tank for air primer system An additional air tank is provided to improve air primer capacity
30-51-7721	1	Trident Automatic Air Primer 3 barrel 3 location with gauge
30-51-8100	1	Heat exchanger included with chassis
30-52-1000	1	Master drain V/V, 12 port
30-52-2000	1	Drain valve for foam system header
30-52-4210	1	Foam System - Hypro FoamPro 2002 Single Tank Plumbed to the two 1-1/2" speedlays, the rear 2-1/2" discharge, the 2-1/2" crosslay the deck gun, and the 1-1/2" front bumper discharge.
30-52-9100	1	Foam concentrate label at foam tank fill
30-52-9200	1	Foam System Instruction Plates
30-52-9400	1	NFPA Foam System certification test
30-60-0510	1	Pneumax Silver 200-SP Compressed Air Foam System
30-60-1000	3	2" CAFS discharge kit for Akron valve For the speedlays and front bumper discharge
30-60-1500	1	2-1/2" CAFS discharge kit for Akron valve For the rear discharge

PART NO	QTY	DESCRIPTION
30-60-1500	1	2-1/2" CAFS discharge kit for Akron valve 2-1/2" crosslay to be foam capable
30-60-2000	1	3" CAFS discharge kit for Akron valve For the deck gun foam line
WATER AND FOAM TANKS		
40-11-2100	1	Polypropylene water tank (Imperial gallons)
40-11-2200	1	Water tank capacity certification (tank manufacturer)
40-11-5500	1	Tank capacity 1200 Imperial Gallons
40-12-5000	1	Foam cell - 30 Imperial gallon
40-21-1000	1	4" tank to pump connection
40-22-0500	1	2" tank fill connection
40-23-0500	1	1" water level gauge connection
40-23-1000	1	1" foam level gauge connection
40-23-1050	1	4" Fireman's Friend connection
40-23-1060	1	10" Newton dump connection At rear of unit in the centre
40-23-1070	1	3" direct fill connection For 2-1/2" direct fills
40-30-0500	1	Sump drain valve (3" gate valve) with linkage
40-30-1000	1	Water Fill Box front left corner
40-31-3500	1	10" rear Newton dump, stainless steel
40-31-3600	1	Newton dump - stainless steel 36" telechute
40-31-4700	1	Newton dump, top mount manual operation
40-31-5610	1	Rotating dump chute for Newton dump SS with telechute
40-31-5800	1	Support for rotating dump chute if necessary Engineering to determine if this support is required
40-31-6010	2	2-1/2" side direct fill - LS and RS panels Equipped with swivel inlet and threaded plug, bleeder
40-31-9000	1	4" Storz rear fill, Fireman's Friend
ELECTRICAL		
50-11-0450	1	Base electrical system - International Diamond Logic multiplex
50-11-0600	1	Warning Light Certification
50-11-0700	1	Low Voltage Electrical system test
50-11-0800	1	Low Voltage Electrical System Documents As required by ULC and NFPA standards
50-11-0900	1	Rocker switch panel with master warning switch Located in chassis dash, Diamond Logic switches ***Rocker switch assignments: MASTER -LIGHT BAR RED -LIGHT BAR WHITE -REAR BEACONS -FLASHING WARNING -REAR FLOODS

PART NO	QTY	DESCRIPTION
50-11-1400	1	Federal PA300 100 watt siren
50-11-1620	1	Siren speaker,100 watt, in front bumper - Federal AS124
50-11-20AA	1	Install customer Federal Q2B siren through front bumper Controlled by foot switch at both driver and officer positions by Metalfab. Install manual shutoff on front of console.
50-11-2600	1	Siren to be accessible to driver and officer
50-11-6138	1	Whelan F4N2QLED 55" LED light bar NFPA 6 red, 2 white 1571201 WECAD confirmed at precon
50-11-6615	1	Rear LED Traffic Advisor warning lights - TAM83 - surface mount - 30.45" long TACTL5 control included, install in cab console
50-11-8600	1	Rear LED beacons-Whelan MCFLED2R (pr) both red
50-12-8520	1	Front LED flashers (pr)-Whelan red LED 600 with integral flasher
50-12-8610	1	Rear LED flashers (pr)-Whelan red LED 600 with integral flasher
50-12-8710	1	Front side inter lts (pr) - Whelan red LED 600 with integral flasher Install in ends of extended front bumper
50-12-8810	1	Body side inter lts (pr)-Whelan red LED 600 with integral flasher
50-12-8905	1	Add'l body side inter lts (pr)-Whelan red LED 600 with integral flasher
50-21-1505	1	Rear floods (pr) Unity LED Note that these lights are also used as rear step lights and cannot be managed
50-21-2541	2	FRC SPECTRA telescoping floods 12 volt Mount on front corners of pump house These lights can be managed Switched on light head Wired to Equipment not stowed light
50-21-5100	1	Compartment lighting - LED tube lights in each compartment (rollup doors)
50-21-5500	1	Door Ajar warning light Warning label in cab to read: "Do Not Move Apparatus when Light is on" Located in chassis dash
50-21-5550	1	Equipment rack not stowed warning light Warning label in cab to read: "Do Not Move Apparatus when Light is on" Located in chassis dash
50-21-5550	1	Equipment rack not stowed warning light Warning label in cab to read: "Do Not Move Apparatus when Light is on"
50-21-8001	1	Step lights for body steps - 4" LED On when park brake is set
50-21-8201	1	Step lights for chassis steps - LED lumabar On when park brake is set Note upper light is included with International chassis

PART NO	QTY	DESCRIPTION
50-21-8600	1	LED clearance lts and reflectors
50-21-8800	1	LED intermediate turn signal/clearance/reflector length >30'
50-22-0700	1	Whelan 64 LED tail/brake-turn-backup module (pr)
50-31-6560	1	Ground lighting (LED Lumabar) - 4 door chassis On when park brake is set
50-31-6570	1	Ground lighting (LED Lumabar) - side mount body On when park brake is set
50-35-0500	1	Installation of customer supplied mobile radio Customer will provide TMR radio Custom Communication to provide the VHF radio to match the Fire Department's current radios and invoice directly to Fire Department - notify Custom Communication of this when setting up installation - they have the frequencies and necessary information to match current installations.. Note that a second antenna will be necessary, we will have to drop the headliner for Custom Communication.
50-35-0560	1	VHF antenna with base - commercial chassis BODY
60-10-1400	1	Single axle extruded aluminum body
60-10-4100	1	No "beavertail" rear step supports
60-10-4600	1	Painted fender surround
60-10-4700	1	Integral aluminum fender trim
60-10-5400	1	Diamondback pumphouse steps
60-10-5430	1	Diamondback 19" rear step
60-10-6000	1	Extruded rub rail
60-11-0300	1	Front left side compartments to top of wheel well
60-11-0550	1	Second front right side compartment to top of wheel well for SCBA tubes
60-11-0700	1	Front right side compartments full height
60-11-1000	1	Rear left side compartments to top of wheel well
60-11-1400	1	Rear right side compartments full height
60-11-1900	1	Low side compartment (up to 18") each over left side rear wheels
60-11-2000	1	High side compartment (over 18") each over right side rear wheels
60-11-3100	1	No rear compartment
60-11-4500	2	Flush mount aluminum door - single with "D" handle L2, R2 Flip up door for L2 Vertical hinged door for R2
60-11-5500	1	Rollup door - standard height R3 Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5510	2	Rollup door - intermediate height L1, L3 Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5520	2	Rollup door - full height R1, R4 Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5530	2	Rollup door - to enclose pump panel Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point

PART NO	QTY	DESCRIPTION
60-11-5654	2	Amdor pull strap not requested
60-11-5654	2	Amdor pull strap not requested
60-11-5655	1	Amdor pull straps - Flex - HD (for door opening 20"-37")
60-11-5660	4	Amdor pull straps - Flex - HD (for door opening 49"-70")
60-31-4100	1	Extruded aluminum handrails Minimum 2" clearance from handrail to any surface One horizontal under the hose bed Two vertical, one each side of hose bed
60-31-5000	1	Zico access Ladder at rear of unit Minimum 7" clearance between rung and any obstruction Includes switch for Equipment not Stowed warning light in cab Includes lighting for steps
60-31-5500	1	Steps at rear of body (folding) right side and centre only Maximum height between steps is 18" Illuminated when park brake is set Include two steps above dump valve for easier opening and closing of the hose bed covers.
60-31-5600	1	Steps and grab handles at front of body next to pump panel Maximum height between steps is 18" Illuminated when park brake is set
60-31-6500	1	Compartment matting - black plastic interlocking tile
60-31-8000	3	BA bottle compt (ea)-fender well For Draeger 4500CF 7-3/4" diameter x 24-7/8" long cylinders
60-31-8700	4	Sliding tray (ea) - 400 pound capacity with gas strut Reflective stripe is applied on the exposed edge for visibility when the compartment door is open At floor level in L1, L3, R1, R3
60-31-8710	2	Adjustable sliding tray with gas strut Install in front LS compartment above existing sliding tray
60-31-8730	1	Floor dry absorbent compartment in fender well LS
60-31-9600	4	Adjustable shelf (ea) Reflective stripe is applied on the exposed edge for visibility when the compartment door is open Shallow in L1, L3, R3, R4
60-31-9600	1	Adjustable shelf (ea) Supply and install additional shelf in R3 compartment, unistruts are already present
60-32-3560	1	Three hose divider (each) Hand hold required in end One fixed in centre, two adjustable
60-32-7500	1	Hose bed - aluminum Main hose bed to be 24" deep

PART NO	QTY	DESCRIPTION
60-33-0000	1	Paint exterior - Imron Elite *** Paint code and colour - To match chassis cab RED
60-33-0200	1	Undercoat vehicle with KROWN rust protection
60-33-0600	1	Chassis wheels not painted
60-33-1000	1	Paint pump and plumbing job colour
60-33-1600	1	Special paint compartment interior - gray zolatone
60-33-2200	1	Lettering - 80 letters up to 3" tall - 3 colour *** Vinyl letters, Fire Department to provide details on location and text.
60-33-3200	1	Reflective stripe - to match M16-18617 50% of perimeter each side and rear, 25% of perimeter front
60-33-3310	1	Reflective stripe - red and yellow chevron at rear 50% of perimeter each side and rear, 25% of perimeter front
60-33-4600	1	Aluminum cover over crosslays - with end tarps (black) End tarps to be fastened with velcro straps similar to M16-18617
60-33-5000	1	Aluminum cover over hose bed with end tarps - black Hose bed lights under hose bed cover, on when park brake is set Hose bed covers wired to door ajar warning light End tarps to be fastened with velcro straps similar to M16-18617
60-40-2000	2	4" Hose tray - top mount (ea) Locate in hose bed on left side, sized for customer supplied Harrington 4" x 10' suction hose
60-40-5500	2	Suction hose tube (each) with door For 80-11-5000 suction hoses
60-40-9000	1	Tube mount for ladders, with rear door For customer supplied Duo Safety ladders - 24' two section extension, 14' roof, and 10' attic ladder; and customer supplied pike poles
60-41-6005	1	Zico horizontal electric portable tank rack To be wired so only operable when park brake is engaged. Flashing lights and reflective tape required at front and rear to indicate any areas that protrude beyond the body. For customer supplied 1500 gallon portable tank - size for our standard
60-41-6010	1	ZICO PTS switched at rear above tail light Switch is located on same side as electric rack
60-91-05AA	1	SCBA storage (3) in R2 compartment For Draeger 4500CF 7-3/4" diameter x 24-7/8" long cylinders
60-91-0800	1	Swing out tool board in R1 compartment
INSTRUMENTATION		
70-11-0000	1	Warning Label on Pump Operator's Panel
70-11-0501	1	Side mount instrument panel with rollup door LS and RS No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position

PART NO	QTY	DESCRIPTION
70-11-1500	1	Stainless steel instrument panels No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position
70-11-3200	1	Colour coded tags
70-11-5100	1	Open storage at rear top of pump house Include drains with hose to below the frame Include interlocking plastic tile for the floor Include lighting for this area, active when park brake is set
70-11-5500	1	Right side pump access door No opening dimension less than 18" Slot required for Primer level viewing
70-11-7500	1	Heat pan-aluminum
70-11-8000	1	Heater in pump compartment
70-20-1120	2	4-1/2" compound gauge - dual face 0-400 Thuemling brand
70-20-2130	10	2-1/2" pressure gauge - dual face 0-400 - Thuemling brand
70-20-2130	1	2-1/2" pressure gauge - dual face 0-400 - Thuemling brand Additional gauge required for second valve for deck gun
70-20-2500	1	Primer control
70-20-2501	2	Additional Primer control
70-20-3300	1	FRC InControl Governor Control Throttle can be no lower than 42" and no higher than 72" from operator's standing position.
70-20-3500	1	Electric water level gauge on pump panel, Class One
70-20-3501	1	Tank level indicator lights - Right side and rear Whelen TIR3 Super LED Each side and rear of body Green, Blue, Amber and Red. To be disabled when chassis park brake is released.
70-20-6500	1	Test gauge panel Mount below the compound gauges for proper draining
70-20-7500	1	Heat exchanger control valve
70-21-1500	1	Electric Foam Level gauge Include access to and room for sender in front of body and back of pump house
70-21-2100	1	PTO Hourmeter
70-21-5500	1	Panel readout for Battery Conditioner Mount on LS cab step trim between front and rear doors next to 120 volt inlet
71-21-31AA	1	Transmission warning light Displayed on InControl
71-21-4000	1	Microphone compartment This compartment is 7" x 6" x 4" deep. Customer to specify if microphone and cable will not fit in this space
71-21-4500	1	Speaker on pump panel
ACCESSORIES		
80-11-5000	2	6" x 10' lightweight suction hose (ea) Mount in 60-40-5500 hose tubes

